



R = Radiused corner

| DIE No. | A | B | C | D | RI | R2 | R3 | kg/m | P |
|-----------------|--------|---|------|------|------|------|----|-------|-----|
| UA 2071 | 10.00 | | 1.60 | | | | | 0.080 | 40 |
| UA 1090 | 12.00 | | 1.60 | | | | | 0.097 | 48 |
| UA 1097 | 12.00 | | 3.00 | | | | | 0.170 | 48 |
| UA 1091 | 15.00 | | 1.60 | | | | | 0.123 | 60 |
| UA 1092 | 20.00 | | 1.60 | | | | | 0.166 | 80 |
| UA 1101 | 20.00 | | 3.00 | | | | | 0.301 | 80 |
| UA 5505 | 22.00 | | 1.60 | | | | | 0.183 | 88 |
| UA 1094 | 25.00 | | 1.60 | | | | | 0.210 | 100 |
| UA 1103 | 25.00 | | 3.00 | | | | | 0.382 | 100 |
| UA 1113 | 25.00 | | 4.50 | | | | | 0.555 | 100 |
| UA 1121 | 25.00 | | 6.00 | | | | | 0.715 | 100 |
| UA 1096 | 30.00 | | 1.60 | | | | | 0.253 | 120 |
| UA 1105 | 30.00 | | 3.00 | | | | | 0.463 | 120 |
| UA 1612 | 30.00 | | 4.50 | | | | | 0.677 | 120 |
| UA 1532 | 30.00 | | 6.00 | | | | | 0.875 | 120 |
| UA 2503 | 30.00 | | 6.00 | 3.00 | 1.50 | F | | 0.853 | 113 |
| AUS 6496 | 32.00 | | 1.60 | | | | | 0.269 | 128 |
| UA 5854 | 32.00 | | 3.00 | 0.50 | 0.50 | 0.50 | | 0.494 | 127 |
| UA 2812 | 35.00 | | 4.50 | | | | | 0.799 | 140 |
| UA 1613 | 38.10 | | 4.75 | | | | | 0.919 | 152 |
| UA 1099 | 40.00 | | 1.60 | | | | | 0.340 | 160 |
| UA 1107 | 40.00 | | 3.00 | | | | | 0.626 | 160 |
| UA 1114 | 40.00 | | 4.50 | | | | | 0.920 | 160 |
| UA 1122 | 40.00 | | 6.00 | | | | | 1.203 | 160 |
| UA 2502 | 40.00 | | 6.00 | 3.00 | 1.50 | F | | 1.178 | 153 |
| UA 1100 | 50.00 | | 1.60 | | | | | 0.426 | 200 |
| UA 2714 | 50.00 | | 2.00 | | | | | 0.531 | 199 |
| UA 1110 | 50.00 | | 3.00 | | | | | 0.788 | 200 |
| UA 5279 | 50.00 | | 4.00 | | | | | 1.036 | 199 |
| UA 1116 | 50.00 | | 4.50 | | | | | 1.164 | 200 |
| UA 1123 | 50.00 | | 6.00 | | | | | 1.523 | 200 |
| UA 3089 | 50.00 | | 6.00 | | 6.00 | | | 1.543 | 197 |
| UA 1129 | 50.00 | | 9.00 | | | | | 2.219 | 200 |
| AUS 6495 | 60.00 | | 3.00 | 0.50 | 0.50 | 0.50 | | 0.947 | 239 |
| UA 1711 | 60.00 | | 6.00 | | | | | 1.853 | 240 |
| UA 1124 | 65.00 | | 6.00 | | | | | 2.016 | 260 |
| UA 3025 | 65.00 | | 6.00 | | 9.60 | | | 2.069 | 255 |
| UA 2167 | 75.00 | | 3.00 | | | | | 1.195 | 300 |
| UA 1526 | 75.00 | | 4.50 | | | | | 1.768 | 300 |
| UA 1126 | 75.00 | | 6.00 | | | | | 2.341 | 300 |
| UA 1527 | 75.00 | | 9.00 | | | | | 3.426 | 300 |
| UA 1712 | 80.00 | | 6.00 | | | | | 2.504 | 320 |
| UA 1127 | 90.00 | | 6.00 | | | | | 2.829 | 360 |
| UA 1118 | 100.00 | | 6.00 | | | | | 3.154 | 400 |



DIAGRAMS ACTUAL SIZE UNLESS OTHERWISE INDICATED. DIAGRAMS ARE SCHEMATIC ONLY AND NOT INTENDED AS SPECIFICATION DRAWINGS.

OAD = OVERALL DIMENSIONS

P = EXT PERIPHERY

© ULLRICH ALUMINIUM CO LTD