



Ullrich Aluminium recommend using 3M™ VHB™ Tape for your bonding applications, including hot and cold temperature applications.

3M™ VHB™ Tapes offers a flexible, durable, versatile and strong bonding option for a multitude of applications.

A specialised selection of VHB tapes can be found on the 3M Stand in any of the Ullrich branches nationwide. Also available are technical data sheets and brochures which feature guidelines for correct application procedures.



- **3M™ 4945 VHB™ Tape** is available in 12.7mm, 19mm & 25.4mm x 33m rolls. 4945 provides excellent adhesion to High Surface Energy plastics with the added feature of plasticiser resistance. Use where high dynamic stresses are involved.

- **3M™ 5952 VHB™ Tape** is a general purpose double sided foam tape. Available in 33m & 13.7m length rolls, it provides excellent adhesion to the widest variety of surfaces including most powder coated paints, metal and glass. It performs well in both exterior and interior applications on both flat and textured surfaces. 33 metre rolls are available in 12.7mm, 19mm & 25.4mm widths. The 13.7 metre rolls are 19mm wide and are featured on the 3M stand.

3M™ 4611 VHB™ Tape A firm double-sided, pressure sensitive, closed-cell acrylic foam tape with a PE film liner, Excellent for bonding metals and other high surface energy materials, high temperature resistance. Only available in 12mm x33m length rolls.



To ensure a strong lasting bond, Ullrich Aluminium recommend you use hIPA clean and Scotch-Brite™ 7447 hand pads in conjunction with VHB™ Tapes.
AVAILABLE ON THE 3M STAND IN YOUR NEAREST ULLRICH BRANCH!



3M VHB Tape turns 30 on November 10 2010!



Go to: www.sealthedeal.co.nz for more information on 3M VHB Tapes